Contemporary Sediment Transport Processes through Submarine Canyon Heads

P. Puig Institut de Ciències del Mar (CSIC) Passeig Marítim de la Barceloneta, 37-49 Barcelona 08003, Spain

phone: +34 93 230 9518 fax: +34 93 230 9555 email: ppuig@icm.csic.es

Grant Number: N00014-04-1-0379 http://www.icm.csic.es

LONG-TERM GOAL

The long-term goal of this research effort is to understand the oceanic processes that transport, erode and deposit sediment within submarine canyon heads, and contribute to the sediment transfer from the shelf to the continental slope.

OBJECTIVES

Several specific objectives are being pursued (1) identify the principal off-shelf sediment transport mechanisms acting within northwestern Mediterranean submarine canyon heads, including short-term (i.e. hours to weeks) and long-term (e.g. seasonal) processes, (2) evaluate the relative importance of different processes in the down-canyon sediment transfer (gravity-driven versus current-driven), (3) study the role of intermediate nepheloid layer detachments as actual transfer pathways of suspended sediment particles from the continental shelf to canyons and (4) provide sediment dynamic constraints for the interpretation of the sedimentary record within submarine canyons.

APPROACH

The proposed technical approach will include the deployment (in the axis of the canyon head) of a BBL tripod at 150-m depth, together with the deployment of two moorings, at 200- and 500-m depth. The tripod will be equipped with a pulse coherent acoustic doppler profiler (PCADP), six optical back-scatter sensors (OBS), an acoustic back-scatter sensor (ABS), an upward-looking acoustic doppler current profiler (ADCP) and an Aanderaa RCM9 current-meter. The shallower mooring will be equipped with an RCM9 current-meter located near the bottom and a string of temperature and turbidity sensors. The deeper mooring will be equipped with an RCM9 current-meter and a sequential sediment trap located near the bottom. This observational effort will have a duration of 8 months to capture seasonally varying processes, and therefore a mid-deployment cruise will be conducted for instrumentation refurbishing. During cruises (instruments deployment, refurbish and recovery), water column measurements will be conducted with a CTD+transmissometer to evaluate the distribution of nepheloid structures within the canyon. This instrument will be able to reach the seabed and it is equipped with a bottom trigger mechanism to collect water samples in the BBL.

The tripod will provide SSC measurements (OBS & ABS) and velocities (PCADP) at numerous heights (< 1 m) above the seabed to investigate the occurrence of down-canyon sediment-gravity flows. The upward-looking ADCP will collect velocity profiles through the entire water column to

a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	Same as Report (SAR)	4		
16. SECURITY CLASSIFIC		17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON		
15. SUBJECT TERMS						
	l of this research eff ithin submarine ca pe.		<u>-</u>		<u>-</u>	
13. SUPPLEMENTARY NO	OTES					
12. DISTRIBUTION/AVAII Approved for publ	LABILITY STATEMENT ic release; distribut	ion unlimited				
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)		
	ZATION NAME(S) AND AI s del Mar (CSIC),Pa 8003, Spain, ,	` '	Barceloneta,	8. PERFORMING REPORT NUMB	G ORGANIZATION EER	
				5f. WORK UNIT NUMBER		
				5e. TASK NUMBER		
4. TITLE AND SUBTITLE Contemporary Sediment Transport Processes through Submarine Canyon Heads 6. AUTHOR(S)				5d. PROJECT NUMBER		
			5c. PROGRAM ELEMENT NUMBER			
			5a. CONTRACT NUMBER 5b. GRANT NUMBER			
1. REPORT DATE 30 SEP 2004		2. REPORT TYPE		3. DATES COVERED 00-00-2004 to 00-00-2004		
maintaining the data needed, and c including suggestions for reducing	lection of information is estimated to ompleting and reviewing the collect this burden, to Washington Headqu uld be aware that notwithstanding and DMB control number.	tion of information. Send commentarters Services, Directorate for Inf	s regarding this burden estimate formation Operations and Reports	or any other aspect of to the state of the s	his collection of information, Highway, Suite 1204, Arlington	

Report Documentation Page

Form Approved OMB No. 0704-0188 determine the influence of the canyon topography on the current direction, particularly above the canyon rims. The RCM9 current-meters placed on the tripod and on the moorings will generate timeseries at high frequencies (i.e. 5-10 minutes) and will provide information on short-term variability in water properties, suspended-sediment concentration and fluxes. The string of temperature+turbidity sensors installed on the mooring will be used to asses the presence of internal waves and identify nepheloid layer detachments, while the sediment trap will collect and characterize near-bottom settling particle fluxes. Additionally, the information derived from the water column profiling will provide relationships between the hydrographic structure and the development of nepheloid layers.




Figure 1. Bathymetric map of the Cap de Creus submarine canyon showing the location of the instruments that will be deployed during autumn-winter 04-05 and the distribution of the CTD casts.

WORK COMPLETED

FY 04 was intended to be a preparation year for the upcoming observational effort beginning in late September 04. In July 04 I attended to a planning meeting in Keystone (CO), in conjunction with other researchers involved in the Gulf of Lions field study, to design the best strategy for tripod and mooring deployments in order to accomplish the general objectives proposed in the EuroStrataform program.

RESULTS

No results yet.

IMPACT/APPLICATION

This effort will characterize the mechanisms responsible for the off-shelf transport of sediment through submarine canyon heads, providing information for the interpretation of the sedimentary record within submarine canyons. The observed processes will be very useful for development and improvement of sediment transport and accumulation models. The identification of sediment-gravity flows in submarine canyons heads will also provide insights for slope stability and submarine canyons formation studies.

TRANSITIONS

None.

RELATED PROJECTS

EU-EuroSTRATAFORM (http://www.soc.soton.ac.uk/CHD/EUROSTRATAFORM/index.html). In addition, this observational effort will be a joint collaboration with other ONR funded researchers, A. Ogston (UW), C. Sherwood (USGS), B.L. Mullenbach (TAMU), C. Nittrouer (UW), as well as with personnel at the University of Perpignan (CEFREM), X. Durrieu de Madron and Serge Heussner.

PUBLICATIONS

None

PATENTS

None

HONORS/AWARDS/PRIZES

None